

DIN 228A




typ

H


 $\lambda=35^\circ$
 $\gamma=6^\circ$

HSS

Co8



Použití / Usage / Domaines d'application / Употребление

1 2 3 4 5 6 7 8 9 10 11 12 13

Krátké / Short / Court / Короткие

D k 10	I	L	MK	Z	CODE
10	22	92	1	4	440248.100
12	26	96	1	4	440248.120
14	26	111	2	4	440248.140
16	32	117	2	4	440248.160
18	32	117	2	4	440248.180
20	38	123	2	4	440248.200
22	38	123	2	5	440248.220
25	45	147	3	5	440248.250
28	45	147	3	5	440248.280
30	45	147	3	6	440248.300
32	53	178	4	6	440248.320
36	53	178	4	6	440248.360
40	63	188	4	6	440248.400
45	63	188	4	6	440248.450
50	75	233	5	6	440248.500

Dlouhé / Long / Long / Длинные

D k 10	I	L	MK	Z	CODE
10	45	115	1	4	441248.100
12	53	123	1	4	441248.120
14	53	138	2	4	441248.140
16	63	148	2	4	441248.160
18	63	148	2	4	441248.180
20	75	160	2	4	441248.200
22	75	160	2	5	441248.220
25	90	192	3	5	441248.250
28	90	192	3	5	441248.280
30	90	192	3	6	441248.300
32	106	231	4	6	441248.320
36	106	231	4	6	441248.360
40	125	250	4	6	441248.400
45	125	250	4	6	441248.450
50	150	308	5	6	441248.500

 Příklad objednávky / Example of order / Exemple de commande / Пример заказа: **440248.100 (+ TiAlN)**

 1
2
3
4
5
6
7
8